NSN 5305-00-670-7127

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-670-7127 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.179 inches **Fastener Length:** Between 0.335 inches and 0.345 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.059 inches and 0.069 inches **First Diameter From Head:** Between 0.248 inches and 0.252 inches **Second Diameter From Head:** 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.114 inches and 0.116 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.045 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-670-7127

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0