Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-674-8540

3a Thread Length: Between 0.140 inches and 0.172 inches Fastener Length: 0.750 inches Head Style: Flat countersunk undercut Head Height: 0.065 inches First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thread y Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Between 0.140 inches and 0.172 inches Fastener Length: 0.750 inches Head Style: Flat countersunk undercut Head Height: 0.065 inches First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Fastener Length:0.750 inchesHead Style:Flat countersunk undercutHead Height:0.065 inchesFirst Diameter From Head:Between 0.114 inches and 0.120 inchesDistance From Largest Bearing Surface OBetween 0.513 inches and 0.545 inchesInternal Drive Style:SlotThread Diameter:0.164 inchesThread Series Designator:UncShelf Life:N/aUnit Of Measure:	
0.750 inches Head Style: Flat countersunk undercut Head Height: 0.065 inches First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thread y Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Head Style: Flat countersunk undercut Head Height: 0.065 inches First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Flat countersunk undercut Head Height: 0.065 inches First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Head Height: 0.065 inches First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
0.065 inches First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
First Diameter From Head: Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Between 0.114 inches and 0.120 inches Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	
Distance From Largest Bearing Surface O Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Between 0.513 inches and 0.545 inches Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Internal Drive Style: Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Head To End Of First Diameter:
Slot Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	
0.164 inches Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Thready Qty Per Inch (tpi): 32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
32 Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Unc Shelf Life: N/a Unit Of Measure:	
Shelf Life: N/a Unit Of Measure:	
N/a Unit Of Measure: 	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	