

View Online at <https://aerobasegroup.com/nsn/5305-00-675-2521>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.265 inches and 0.297 inches

Fastener Length:

3.258 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.264 inches and 0.266 inches

Head Height:

Between 0.141 inches and 0.169 inches

First Diameter From Head:

0.156 inches

Second Diameter From Head:

Between 0.245 inches and 0.255 inches

Third Diameter From Head:

0.156 inches

Fourth Diameter From Head:

Between 0.245 inches and 0.255 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 1.320 inches and 1.336 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.382 inches and 1.398 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

2.891 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

2.953 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 303

Material Specification:

66 federal standard single material response

Surface Treatment:

Passivate and paint

Surface Treatment Specification:

580-0025-00 fscm 90107 mfr ref all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0