NSN 5305-00-675-2522

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-675-2522 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.219 inches **Fastener Length:** Between 4.463 inches and 4.468 inches **Head Style:** Flat chamfer **Head Diameter:** 0.234 inches **Head Height:** Between 0.188 inches and 0.193 inches **First Diameter From Head:** 0.234 inches **Second Diameter From Head:** 0.141 inches **Third Diameter From Head:** 0.234 inches **Fourth Diameter From Head:** 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.775 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 3.812 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 4.187 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

NSN 5305-00-675-2522

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
580-0025-00 fscm 13499 mfr ref single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0