NSN 5305-00-679-6192

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-679-6192 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.485 inches and 0.536 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **Hole Diameter:** 0.046 inches First Diameter From Head: Between 0.125 inches and 0.127 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.089 inches and 0.099 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 **Material Specification:** Isi assn standard single material response **Surface Treatment:** Cadmium and chromate **Thread Series Designator:**

Unc

NSN 5305-00-679-6192

Externally Relieved Body Screw - Page 2 of 2



Sł	elf	L	ife:
N/a			

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0