## NSN 5305-00-680-5448

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-680-5448 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.160 inches and 0.180 inches **Fastener Length:** Between 0.250 inches and 0.270 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **Hole Diameter:** 0.046 inches First Diameter From Head: Between 0.137 inches and 0.139 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.070 inches and 0.100 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 430 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** 

Unf

## NSN 5305-00-680-5448

Externally Relieved Body Screw - Page 2 of 2



Shelf	Life:
Onch	LIIC.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0