## NSN 5305-00-680-5923

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-680-5923

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.425 inches	
Fastener Length:	
Between 1.4725 inches a	nd 1.5025 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.455 inches and	1 0.510 inches
Grip Diameter:	
Between 0.2485 inches a	nd 0.2495 inches
nternal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.2500 inches	
Grip Length:	
Between 1.0525 inches a	nd 1.0725 inches
Thready Qty Per Inch (tp	i):
28	
Countersink Angle:	
Between 99.0 degrees an	d 101.0 degrees
Material:	
Steel comp e4340 or stee	el comp 8740
Material Specification:	
√il-s-5000 military specifi	cation 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Spec	ification:
Qq-p-416, type 2 class 2	federal specification single treatment response
Thread Series Designate	or:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

## NSN 5305-00-680-5923

Close Tolerance Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5000 spec.

