NSN 5305-00-680-6121

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-680-6121 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.562 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.102 inches and 0.113 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 20.0 rockwell c primary washer and 26.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.372 inches and 0.383 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.022 inches Material: Steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 **Material Specification:** Sae assn standard single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-680-6121

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0