NSN 5305-00-680-6355



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-680-6355 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.878 inches and 2.000 inches **Fastener Length:** Between 1.940 inches and 2.000 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
--Demilitarization:
No
Fiig:

A500d0

NSN 5305-00-680-6355

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.