# NSN 5305-00-680-6937

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-680-6937



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### **Thread Length:**

Between 0.189 inches and 0.301 inches

#### Fastener Length:

Between 1.886 inches and 1.916 inches

#### Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

#### **Head Height:**

Between 0.122 inches and 0.133 inches

### Internal Drive Style:

Cross recess type 1

# Thread Diameter:

0.190 inches

## Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

### **Screw Material:**

Steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037

### Screw Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military

specification 3rd material response or mil-s-8503 military specification 4th material response

#### Screw Surface Treatment:

Cadmium and chromate

### **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A500d0

## Mil-std (military Standard):

Mil-s-5000 spec.