Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-680-9197

·	
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.624 inches	
Fastener Length:	
0.750 inches	
Head Style:	
Fillister	
Head Diameter:	
Between 0.389 inche	es and 0.414 inches
Head Height:	
Between 0.155 inche	es and 0.170 inches
Washer Quantity:	
1	
Internal Drive Style	:
Cross recess type 1	
Thread Diameter:	
0.250 inches	
Thready Qty Per Inc	ch (tpi):
20	
Hardness Rating:	
45.0 rockwell c prim	nary washer and 53.0 rockwell c primary washer
Primary Washer Ou	utside Diameter:
Between 0.384 inche	es and 0.400 inches
Primary Washer St	yle:
Split helical ring	
Primary Washer Ma	aterial Thickness:
0.063 inches	
Material:	
Steel comp 1010 fas	stener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener
or steel comp 1017 f	fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener
Surface Treatment:	
Cadmium or zinc	
Surface Treatment	Specification:
Qq-p-416, type 1, cl	3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Series Desi	gnator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5305-00-680-9197

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

