NSN 5305-00-682-5695

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-682-5695

| T | Fhread Class: |
|---|---|
| 2 | 2a |
| T | Thread Direction: |
| F | Right-hand |
| ٦ | Thread Length: |
| С | 0.153 inches |
| F | Fastener Length: |
| С | 0.1875 inches |
| ŀ | lead Style: |
| F | Tat countersunk |
| ŀ | lead Diameter: |
| E | Between 0.105 inches and 0.119 inches |
| h | nternal Drive Style: |
| S | Slot |
| T | Thread Diameter: |
| С | 0.060 inches |
| T | Thready Qty Per Inch (tpi): |
| 8 | 30 |
| C | Countersink Angle: |
| 8 | 32.0 degrees |
| S | Screw Material: |
| S | Stainless steel |
| S | Screw Material Specification: |
| C | Qq-s-763 federal specification single material response |
| S | Screw Surface Treatment: |
| F | Passivate |
| T | Thread Series Designator: |
| ι | Jnf |
| | Specification Or Standard: |
| I | type and 2s style |
| S | Shelf Life: |
| ١ | N/a |
| ι | Jnit Of Measure: |
| - | - |
| C | Demilitarization: |
| ١ | ю |
| F | iig: |
| A | \500d0 |