## NSN 5305-00-682-7753

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-682-7753

Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
0.875 inches			
Fastener Length:			
Between 1.234 inches and 1.281 inches			
Head Style:			
Flat chamfer			
Head Diameter:			
Between 0.303 inches and 0.312 inches			
Head Height:			
Between 0.185 inches and 0.190 inches			
Hole Diameter:			
0.047 inches			
Internal Drive Style:			
Hexagon			
Thread Diameter:			
0.190 inches			
Width Across Flats:			
Between 0.156 inches and 0.159 inches			
Hole Quantity:			
6			
Hole Type:			
Drilled			
Thready Qty Per Inch (tpi):			
32			
Min. Tensile Strength (psi):			
80000 pounds per square inch			
Hardness Rating:			
80.0 rockwell b			
Minimum Yield Strength:			
30000 pounds per square inch			
Hole Configuration Style:			
Round internal hexagon			
Material:			
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316			
Material Specification:			
66 federal standard all material responses			
Surface Treatment:			
Passivate			

## NSN 5305-00-682-7753

Socket Head Cap Screw - Page 2 of 2



Surface	<b>Treatment</b>	Specifi	cation:
Juliace	I I Callillelli	Specili	calion.

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0