NSN 5305-00-685-1598

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-685-1598 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.160 inches **Fastener Length:** 0.825 inches **Head Style:** Hexagon **Head Height:** 0.190 inches Width Between Flats: 0.375 inches **Hole Diameter:** 0.047 inches First Diameter From Head: Between 0.185 inches and 0.195 inches **Second Diameter From Head:** Between 0.131 inches and 0.141 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.570 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Hole Quantity: Hole Type:** Thready Qty Per Inch (tpi): 24 **Hole Configuration Style:** Hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Cone point Material:

Steel comp 303

NSN 5305-00-685-1598

Externally Relieved Body Screw - Page 2 of 2



Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0