

View Online at <https://aerobasegroup.com/nsn/5305-00-685-1805>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.358 inches

**Fastener Length:**

4.438 inches

**Head Style:**

Fillister countersunk

**Head Diameter:**

0.274 inches

**Head Height:**

Between 0.133 inches and 0.156 inches

**First Diameter From Head:**

0.163 inches

**Second Diameter From Head:**

0.116 inches

**Third Diameter From Head:**

0.163 inches

**Fourth Diameter From Head:**

0.223 inches

**Fifth Diameter From Head:**

0.163 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

3.250 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

3.281 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

3.938 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

4.000 inches

**Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:**

4.078 inches

**Internal Drive Style:**

Cross recess type ii

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

5

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0