## NSN 5305-00-685-1805

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-685-1805 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.358 inches **Fastener Length:** 4.438 inches **Head Style:** Fillister countersunk **Head Diameter:** 0.274 inches **Head Height:** Between 0.133 inches and 0.156 inches **First Diameter From Head:** 0.163 inches **Second Diameter From Head:** 0.116 inches **Third Diameter From Head:** 0.163 inches **Fourth Diameter From Head:** 0.223 inches Fifth Diameter From Head: 0.163 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 3.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.281 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: **3.938** inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 4.078 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi):

**Externally Relieved Body Diameter Quantity:** 

## NSN 5305-00-685-1805

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp 303
Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0