## NSN 5305-00-685-2375

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-685-2375 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 1.468 inches **Head Style:** Fillister countersunk **Head Diameter:** 0.274 inches **Head Height:** 0.133 inches **First Diameter From Head:** Between 0.157 inches and 0.163 inches **Second Diameter From Head:** 0.125 inches **Third Diameter From Head:** 0.223 inches **Fourth Diameter From Head:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.344 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.969 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.031 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 1.093 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 90.0 degrees **Externally Relieved Body Diameter Quantity:** 

**Product Name:** 

Navy special project

## NSN 5305-00-685-2375

Externally Relieved Body Screw - Page 2 of 2



Material:
Stainless steel
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0