## NSN 5305-00-685-2539

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-685-2539

Thread Class.
Thread Class:
3a
Thread Direction:
Right-hand Thread Lawrith:
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 0.386 inches and 0.416 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.328 inches and 0.385 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unjf
Specification Data:
80205-nas1203 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-00-685-2539

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0