## NSN 5305-00-685-2977

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-685-2977 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.062 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.625 inches **Head Height:** 0.370 inches **First Diameter From Head:** 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.680 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 316 **Material Specification:** Mil-s-7720 military specification 1st material response or astm a582 assn standard 2nd material response or astm a582 assn standard 3rd material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-685-2977

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.