Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-685-3013

| Thread Class: |
|--|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.695 inches |
| Fastener Length: |
| 0.750 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.365 inches and 0.375 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Hole Diameter: |
| 0.050 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| Between 0.188 inches and 0.190 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 43.0 rockwell c |
| Minimum Yield Strength: |
| 130000 pounds per square inch |
| Hole Configuration Style: |
| Round internal hexagon |
| Material: |
| Steel |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| |

NSN 5305-00-685-3013

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0