## NSN 5305-00-685-7778

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-685-7778 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **First Diameter From Head:** 0.190 inches **Second Diameter From Head:** Between 0.135 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.030 inches and 0.050 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.250 inches and 0.270 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 430 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-685-7778

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0