NSN 5305-00-685-8032

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-685-8032



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.998 inches and 1.058 inches

Fastener Length:

Between 1.065 inches and 1.125 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.195 inches and 0.225 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305

Screw Material Specification:

Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 military specification 5th material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-00-685-8032

Machine Screw - Page 2 of 2

Mil-std (military Standard):

spec.

