## NSN 5305-00-688-1220

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-688-1220 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.116 inches **Fastener Length:** 0.234 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.210 inches and 0.225 inches **Head Height:** Between 0.055 inches and 0.067 inches **First Diameter From Head:** Between 0.080 inches and 0.084 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.050 inches and 0.055 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Aluminum alloy 2024 **Material Specification:** Ams 4120 assn standard single material response **Surface Treatment:** Anodize **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-688-1220

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0