NSN 5305-00-688-7032

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-688-7032

Thread Class:

| 3a |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.680 inches |
| Fastener Length: |
| Between 1.090 inches and 1.110 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.178 inches and 0.198 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.070 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.250 inches |
| Hole Quantity: |
| 2 |
| Thready Qty Per Inch (tpi): |
| 20 |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Screw Material: |
| Steel comp 8740 |
| Screw Material Specification: |
| Ams 6322 assn standard single material response |
| Screw Surface Treatment: |
| Cadmium |
| Head Hole Configuration Style: |
| Hexagon flats |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

NSN 5305-00-688-7032

Machine Screw - Page 2 of 2



Fiig:

A500d0