Socket Head Cap Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-688-7689

Tread Direction: Right-hand Tread Length: Between 0.060 inches and 0.150 inches Fastener Length: Between 0.157 inches and 0.180 inches Head Style: Flat counters unk undercut Head Diameter: Between 0.038 inches and 0.025 inches Head Height: Between 0.038 inches and 0.027 inches Locking Feature: Distribution of the state of t
Right-hand Right-hand Thread Length: Batween 0.060 inches and 0.150 inches Fastener Length: Batween 0.157 inches and 0.188 inches Head Siyle: Filt countersunk undercut Head Diamote: Batween 0.038 inches and 0.225 inches Head Height: Between 0.038 inches and 0.047 inches Locking Feature: Stip threads Dirther Style: Cross necess type 1 Thread Dirthe Style: Cross necess type 1 Thread Dirther Style: Cross necess type 1 Thread Dirther Style: Cross necess type 1 Thread Dirther Style: Cross necess type 1 Stread Diameter: Ottower Style: Cross necess type 1 Thread Diameter: Ottower Style: Cross necess type 1 Thread Strength (ngl): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material Stread Foolitation 1st material response or qop-s-764 federal specification 2nd material response
Right-hand Thread Length: Between 0.050 inches and 0.150 inches Fastener Length: Between 0.157 inches and 0.188 inches Head Style: Flat countersum, underout Head Heigh: Between 0.038 inches and 0.225 inches Head Heigh: Between 0.038 inches and 0.255 inches Head Heigh: Between 0.038 inches and 0.471 inches Locking Feature: Strip Heads Cross recess type 1 Cross recess type 1 Cross recess type 1 Thread Diameter: 0.112 inches Thread Strength (ps): Strop Per Inch (ps): Strop Per Inch (ps): Bottwens 0.00 agrees and 82.0 degrees Min Tensile Strength (ps): Bottwens 0.0 degrees and 82.0 degrees Material: Stel comp 10 or steel comp 416 Mereire Qastreats Steriet Tensethere: Steriet Tensethere: Pread Steledies Designator: Incarestreet: Stel comp 10 or steel comp 416 Materi Pread Teretement: </td
Tread Length: Between 0.060 inches and 0.150 inches Faster Length: Batween 0.157 inches and 0.188 inches Head Skye: Flat countersumk undercut Head Diamoter: Between 0.036 inches and 0.225 inches Head Height: Between 0.388 inches and 0.247 inches Head Height: Between 0.388 inches and 0.047 inches Locking Feature: Strip threads Internal Drive Style: Cross receases type 1 Thread Vier Price (Pip): 0.112 inches Thread Vier Price (Pip): 0.000 pounds per square inch Countersink Angle: Between 0.00 degrees and 82.0 degrees Material: Stel com 1.01 stel comp 1.6 Stel com 1.01 stel comp 1.6 Pastwate Pastwate Direct Teatment: Pastwate Direct Teatment: Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Stel com 1.01 stel comp 1.6 Pastwate Pastwate Pastwate <t< td=""></t<>
Between 0.050 inches and 0.150 inches Fastener Length: Between 0.157 inches and 0.188 inches Head Style: Fast countersumk underout Head Diameter: Between 0.038 inches and 0.225 inches Head Height: Between 0.038 inches and 0.255 inches Head Hoight: Between 0.038 inches and 0.047 inches Between 0.038 per square inch Between 80.0 degrees and 82.0 degrees Between S0.0 degrees Between S0.0 degrees Andero Andero An
Pasteer Length: Between 0.157 inches and 0.188 inches Head Style: Flat countersuuk underout Head Diameter: Between 0.195 inches and 0.225 inches Head Righ: Between 0.038 inches and 0.047 inches Locking Feature: Strip theads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread You Per Inch (pi): 40 8000 pounds per square inch Stropter Style: Countersiuk Angle: Between 80.0 degrees and 82.0 degrees Material: Stropter Style: Curder Stropter (psi): Stropter Stropter (psi): Stropter Stropter (psi): Bottomare Stropter (psi):
Between 0.157 inches and 0.188 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.195 inches and 0.225 inches Between 0.038 inches and 0.225 inches Head Height: Between 0.038 inches and 0.047 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Yer Inch (tpl): 0.112 inches Min. Ensile Strength (ssl): Countersunk Angle: Between 80.0 degrees and 82.0 degrees Material Stel comp 410 or steel comp 416 Material Stel comp 410 or steel comp 416 Material Stread Streads Internal Specification 1st material response or qq-s-764 federal specification 2nd material response Stread Stread Streads Internal Stread Streads Internal Streads Internal Steel specification 1st material response or qq-s-764 federal specification 2nd material response Internal Stread Streads Internal Streads Internation Interna
Head Style: Flat countersunk undercut Head Diameter: Between 0.195 inches and 0.225 inches Head Height: Between 0.038 inches and 0.047 inches Head Style: Cocking Feature: Strip threads Internal Drive Style: Cors recess type 1 Thread Diameter: 0.112 inches Min Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material Steel comp 410 or steel comp 416 Material Specification: Ques-Pa5 Idederal specification 1st material response or qq-s-764 federal specification 2nd material response Passivate Thread Series Designator: Na Unit Measure: Na Unit Measure: Na Unit Measure: Na Head Street Comp 410 Head Steel comp 416 Material Specification Head Steel comp 416 Material Specification Head Steel comp 416 Material Specification
Flat countersunk undercut Head Diameter: Between 0.195 inches and 0.225 inches Head Height: Between 0.038 inches and 0.047 inches Locking Feature: Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Pinneh (pi): 0112 inches Bottom pinneh (pi): 000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material Specification Carder Teatment: Passivate Thread Selies Designator: Un Mariel Carder Teatment: Passivate Interal Specification 1st material response or qq-s-764 federal specification 2nd material response Passivate Thread Selies Designator: Va Un C Sheft Inf: Na Lot Inf Measure: Va Lind Measure: Passivate Direct Passivate Infersion: Na Direct Passivate Infersion: Na Direct Passivate Infersion: Na Direct Passivate Infersion: Na Infersion: Na Infersion: Na Infersion: Na Infersion: Na Infersion:
Head Diameter: Between 0.195 inches and 0.225 inches Head Height: Between 0.038 inches and 0.047 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Min. Tonslie Strength (psi): 8000 pounds per square inch Countersink Angle: Betwen 0.10 or steel comp 416 Material: Ques-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response or qq-s-764 federal spe
Between 0.195 inches and 0.225 inches Head Height: Between 0.038 inches and 0.047 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: O.112 inches Thread Vip Per Inch (tpl): 40 Min. Tensile Strength (psi): 80000 pounds per square inch Courters ink Angle: Between 0.014 or steel comp 416 Material: Steel comp 410 or steel comp 416 Material: Passivate Praced Series Designator: Passivate Thread Series Designator: Na Chif Life: Na Dird Measure: Fassivate Thread Series Designator: Na Dird Measure: Na Dird Measure: Passivate Theread Series Designator: Na Dird Measure: Na Dird Measure: Na Dird Measure: Na
Head Height: Between 0.038 inches and 0.047 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Vip Per Inch (tpi): 0 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material Steel comp 410 or steel comp 416 Material Steel comp 410 or steel comp 416 Material Passivate Thread Steel Steingnator: Passivate Streed Testenent: Passivate Thread Steingnator: Nic Grif Elfie: Nic Nic Thread Steingnator: Nic Material Reservection Stef Lifie: Nic Stef Lifie: Nic Stef Lifie: Nic Stef Lifie: Nic St
Between 0.38 inches and 0.047 inches Locking Feature: Stip threads Internal Drive Style: Cross recess type 1 Cross recess type 1 Thread Diameter: O.112 inches Thread V Per Inch (tpi): O.12 inches Thready Oty Per Inch (tpi): O.12 inches Thready Oty Per Inch (tpi): O.12 inches Min. Tensile Strength (psi): Stood pounds per square inch Coursrink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification 1st material response or qq-s-764 federal specification 2nd material response O qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Grade Treatment: Passivat Thread Series Designator: Unc Shelf Life: Na Material Na
Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Oty Per Inch (tpi): 40 Min. Tenslie Strength (psi): 80000 pounds per square inch Countersink Angle: Betwen 80.0 degrees and 82.0 degrees Material Steel comp 410 or steel comp 416 Material Specification Stardes Textement: Passivate Cheid Steil Ste
Strip threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.112 inchesThready Oty Per Inch (tpi):40Min Tensile Strength (psi):80000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesMaterial:Steel comp 410 or steel comp 416Material SpecificationQras-r63 federal specification 1st material response or qq-s-764 federal specification 2nd material responsePassivateThread Series Designator:UncStelf Life:NatNatDird Measure:NatDird Measure:Thread Series Designator:NatDird Measure:PassivateDird Life:NatDird Measure:Thread Series Designator:NatDird Measure:Thread Series Designator:Thread Series Designator:Thread Series Designator:Dird Measure:Thread Series Designator:Thread Series Designator:Dird Measure:Thread Series Designator:Thread Series Designator:Dird Measure:Thread Series Desig
Iternal Drive Style: Cross recess type 1 Thread Diamete: 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification: Qres-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Strate Treatment: Passivate Thread Series Designator: Que Thread Series Designator: Na Dird Life: Na Dird Measure: Pasivate Dird Measure: <t< td=""></t<>
Cross recess type 1 Thread Diameter: O.112 inches Chready Qty Per Inch (tpi): Thready Qty Per Inch (tpi): O Min. Tensile Strength (psi): Min. Tensile Strength (psi): Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification Que-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Pasivate Thread Series Designator: Unc Shelf Life: Na Unc Shelf Life: Na Unc Chreise: Chr
Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification: Qu-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Passivate Thread Series Designator: Unc Shelf Life: Na Unc Shelf Life: Na Did Measure: Did Of Measure: Tread Suite: Na Dif Jensile: Na Dir of Measure: Toto federal specification: Thread Series Designator: Na Dir of Measure: Dir of Measure: Thread Series Designator: Thread Series Designator: Na Dir of Measure: Dir of Measure: Dir of Measure:
0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: 8etween 80.0 degrees and 82.0 degrees Material: 8ete comp 410 or steel comp 416 Material Specification Aqe-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Gurface Treatment: Passivate Thread Series Designator: Unc Sheff Life: N/a Unc Sheff Life: N/a Unc Final Component Compone
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification: Ques-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Designator: Material Direct Sense: Mac Mac
40 Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Bete comp 410 or steel comp 416 Material Specification Gq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Gy-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Material: Passivate Thread Series Designator: Unc Shelf Life: Na Unc Shelf Life: Na Dit of Measure:
Min. Tensile Strength (psi): 80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Strace Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - - Partice Tentent: Pine Compare Com
80000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Life: N/a Lift Of Measure:
Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Dread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Between 80.0 degrees and 82.0 degrees Material: Steel comp 410 or steel comp 416 Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Material: Steel comp 410 or steel comp 416 Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel comp 410 or steel comp 416 Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Shelf Life: N/a Unit Of Measure: Demilitarization:
N/a Unit Of Measure: Demilitarization:
Unit Of Measure: Demilitarization:
 Demilitarization:
Fiig:
A003b0