NSN 5305-00-689-4376

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-689-4376 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.090 inches and 0.096 inches **Fastener Length:** Between 0.384 inches and 0.401 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.122 inches and 0.128 inches **Head Height:** Between 0.042 inches and 0.048 inches **First Diameter From Head:** Between 0.069 inches and 0.075 inches **Second Diameter From Head:** Between 0.0925 inches and 0.0933 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.028 inches and 0.034 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.279 inches and 0.285 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 302 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-689-4376

Externally Relieved Body Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0