## NSN 5305-00-689-9309

As modified by material

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-689-9309

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.187 inches  |
| Fastener Length:  |
| 0.187 inches  |
| Head Style:   |
| Flat chamfer  |
| Head Diameter:  |
| Between 0.154 inches and 0.161 inches   |
| Head Height:  |
| Between 0.095 inches and 0.099 inches   |
| Internal Drive Style:   |
| Hexagon   |
| Thread Diameter:  |
| 0.099 inches  |
| Width Across Flats:   |
| Between 0.078 inches and 0.079 inches   |
| Thready Qty Per Inch (tpi):   |
| 48  |
| Min. Tensile Strength (psi):  |
| 80000 pounds per square inch  |
| Hardness Rating:  |
| 80.0 rockwell b   |
| Minimum Yield Strength:   |
| 30000 pounds per square inch  |
| Material:   |
| Steel comp 303 or steel comp 302 or steel comp 304  |
| Material Specification:   |
| Astm a582 assn standard 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification |
| 3rd material response   |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response   |
| Thread Series Designator:   |
| Unc   |
| Specification Or Standard:  |
| 6 type  |
| Departure From Cited Designator:  |

## NSN 5305-00-689-9309

Socket Head Cap Screw - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0