

View Online at <https://aerobasegroup.com/nsn/5305-00-689-9973>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.365 inches and 0.385 inches

Fastener Length:

Between 1.573 inches and 1.613 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.490 inches and 0.510 inches

Head Height:

Between 0.146 inches and 0.166 inches

Shoulder Diameter:

0.281 inches first shoulder

Shoulder Length:

1.208 inches first shoulder and 1.228 inches first shoulder

Shank Unthreaded Hole Diameter:

0.067 inches first hole and 0.078 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.385 inches first hole and 1.425 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Chromium or cadmium

Surface Treatment Specification:

Qq-c-320-class 2 federal specification 1st treatment response or qq-p-416, type 1, class b federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.