## NSN 5305-00-690-6444

--

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-690-6444

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.407 inc	hes and 0.500 inches
Fastener Length:	
Between 0.469 inc	hes and 0.500 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.357 inc	hes and 0.373 inches
Head Height:	
Between 0.122 inc	hes and 0.133 inches
Internal Drive Sty	le:
Cross recess type	1
Thread Diameter:	
0.190 inches	
Thready Qty Per I	nch (tpi):
32	
Min. Tensile Stre	ngth (psi):
160000 pounds pe	r square inch
Hardness Rating:	
36.0 rockwell c ar	nd 40.0 rockwell c
Surface Finish:	
32.0 microinches t	nreads
Material:	
Steel comp 4140	or steel comp e4340 or steel comp 8740
Material Specifica	ition:
Mil-s-5626 military	specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd m	aterial response
Surface Treatmer	ıt:
Cadmium and chr	omate
Surface Treatmer	It Specification:
Qq-p-416 type 2 c	l 2 federal specification single treatment response
Thread Series De	signator:
Unjf	
Specification Dat	a:
80205-nas1190 pr	ofessional/industrial association standard
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5305-00-690-6444

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.