NSN 5305-00-695-6208

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-695-6208 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.354 inches and 0.396 inches **Fastener Length:** Between 1.359 inches and 1.391 inches **Head Style:** Hexagon **Head Height:** Between 0.188 inches and 0.219 inches Width Between Flats: Between 0.422 inches and 0.453 inches **First Diameter From Head:** Between 0.165 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.005 inches and 0.995 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 **Material Specification:** Q-s-634 assn standard 13th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-695-6208

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0