NSN 5305-00-696-5287

Assembled Washer Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-696-5287 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.503 inches **Fastener Length:** 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.452 inches and 0.507 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Primary Washer Outside Diameter:** Between 0.275 inches and 0.289 inches **Primary Washer Style:** Countersink external teeth **Primary Washer Material Thickness:** Between 0.019 inches and 0.025 inches Material: Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer **Surface Treatment:** Cadmium or zinc **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization: