Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-696-5291

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
1.750 inches	
Fastener Length:	
Between 2.906 inches and 3.000 inches	
Head Style:	
Hexagon	
Head Height:	
Between 0.208 inches and 0.230 inches	
Width Between Flats:	
Between 0.489 inches and 0.500 inches	
Washer Quantity:	
1	
Internal Drive Style:	
Slot	
Thread Diameter:	
0.312 inches	
Thready Qty Per Inch (tpi):	
24	
Hardness Rating:	
30.0 rockwell c fastener and 50.0 rockwell c fastener	
Primary Washer Outside Diameter:	
Between 0.567 inches and 0.590 inches	
Primary Washer Style:	
Flat external teeth	
Primary Washer Material Thickness:	
Between 0.028 inches and 0.034 inches	
Special Features:	
W/header point	
Material:	
Steel comp 1050 primary washer	
Surface Treatment:	
Cadmium or zinc	
Surface Treatment Specification:	
Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response	onse
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	

NSN 5305-00-696-5291

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0