NSN 5305-00-696-5294

Assembled Washer Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-696-5294 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.400 inches **Fastener Length:** 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.155 inches and 0.170 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Primary Washer Outside Diameter:** Between 0.466 inches and 0.478 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.025 inches Material: Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer **Surface Treatment:** Cadmium or zinc **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A003b0

No