## NSN 5305-00-701-6980



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-701-6980 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.845 inches and 0.875 inches **Fastener Length:** Between 3.345 inches and 3.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.977 inches and 1.000 inches **Head Height:** Between 0.490 inches and 0.500 inches **Shoulder Diameter:** 0.746 inches first shoulder and 0.748 inches first shoulder **Shoulder Length:** 2.500 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: 0.375 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 35.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-00-701-6980

Shoulder Screw - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A003b0