## NSN 5305-00-701-7779

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-701-7779 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.972 inches and 2.002 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 7620 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp 4130 **Material Specification:** Mil-s-6758 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

## NSN 5305-00-701-7779

Close Tolerance Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.