NSN 5305-00-702-1299

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-702-1299

View Online at https://aerobasegroup.com/nsn/5305-00-702-1299
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.294 inches and 0.365 inches
Fastener Length:
Between 0.365 inches and 0.395 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.367 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.188 inches and 0.190 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
75000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 302 or steel comp 303 or steel comp 304
Material Specification:
Aisi assn standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas608 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-00-702-1299

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0