NSN 5305-00-704-7952

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-704-7952 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.316 inches and 0.331 inches **Fastener Length:** Between 0.737 inches and 0.747 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.279 inches and 0.283 inches **Head Height:** Between 0.041 inches and 0.051 inches **Shoulder Diameter:** 0.183 inches first shoulder and 0.185 inches first shoulder **Shoulder Length:** 0.385 inches first shoulder and 0.390 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A003b0

NSN 5305-00-704-7952

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.