## NSN 5305-00-707-3658

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-707-3658 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.105 inches and 1.250 inches **Fastener Length:** Between 1.188 inches and 1.250 inches **Head Style:** Pan **Head Diameter:** Between 0.716 inches and 0.740 inches **Head Height:** Between 0.244 inches and 0.261 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5305-00-707-3658** Machine Screw - Page 2 of 2



Fiig:

A500d0