## NSN 5305-00-708-7697

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-708-7697

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.363 inches
Fastener Length:
Between 0.511 inches and 0.541 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Locking Feature:
Patch threads or strip threads
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.138 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:

80205-nas1171 professional/industrial association standard

## NSN 5305-00-708-7697

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0