

View Online at <https://aerobasegroup.com/nsn/5305-00-715-2048>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.875 inches

Fastener Length:

0.875 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.359 inches and 0.385 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

60000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 or steel or steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015

Screw Material Specification:

Qq-s-634 federal specification 1st material response or qq-s-634 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-637 federal specification 17th material response or 66 federal standard 18th material response or 66 federal standard 19th material response or 66 federal standard 20th material response or 66 federal standard 21st material response or 66 federal standard 22nd material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Special Features:

Material, st1016, st1017, st1018, st1019, st1020, st1022, st1137 doc. And class. Federal standard 66, st0015, fed standard 66, b1122, st0016, fed standard 66, b1123

Thread Series Designator:

Fig:

A500d0