NSN 5305-00-715-7146

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-715-7146 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.296 inches and 0.328 inches **Fastener Length:** Between 1.172 inches and 1.203 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.609 inches and 0.641 inches **Head Height:** Between 0.359 inches and 0.391 inches **First Diameter From Head:** Between 0.359 inches and 0.391 inches **Second Diameter From Head:** Between 0.180 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.047 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.859 inches and 0.891 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303se **Material Specification:** Aisi assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** +4a g+2-+2 fscm 03538 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-715-7146

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0