NSN 5305-00-718-9829

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-718-9829 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.339 inches and 0.375 inches **Fastener Length:** 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.156 inches and 0.172 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 1010 **Screw Material Specification:** Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Special Features:** Fleet ballistic missile quality as identified by quality control no.Poso912922 **Thread Series Designator:** Unc **Departure From Cited Designator:** As modified by special features Shelf Life: N/a

Demilitarization: No

Unit Of Measure:

NSN 5305-00-718-9829 Machine Screw - Page 2 of 2



Fiig:

A500d0