

View Online at <https://aerobasegroup.com/nsn/5305-00-719-6407>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.484 inches and 0.516 inches

Fastener Length:

Between 7.078 inches and 7.109 inches

Head Style:

Fillister

Head Diameter:

Between 0.389 inches and 0.414 inches

Head Height:

Between 0.161 inches and 0.170 inches

First Diameter From Head:

Between 0.223 inches and 0.249 inches

Second Diameter From Head:

0.250 inches

Third Diameter From Head:

Between 0.182 inches and 0.192 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.641 inches and 0.672 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.766 inches and 0.797 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 6.578 inches and 6.609 inches

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Externally Relieved Body Diameter Quantity:

1

Product Name:

Navy special project

Material:

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347

Material Specification:

Qq-s-763 federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Dd7580 fscm 10001 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0