Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-720-8787

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.562 inches
Fastener Length:
1.312 inches
Head Style:
Fillister
Head Diameter:
Between 0.208 inches and 0.226 inches
Head Height:
Between 0.086 inches and 0.096 inches
First Diameter From Head:
Between 0.093 inches and 0.103 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.750 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 1008 or steel or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050

Material Specification:

Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 2nd material response or qq-s-637 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-634 federal specification 18th material response or qq-s-634 federal specification 19th material response

Surface Treatment:

Chromate zinc

Thread Series Designator:

Unc

Chalf I ifar