NSN 5305-00-721-3057

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-721-3057 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.636 inches and 0.666 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.280 inches and 0.337 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1202 professional/industrial association standard Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-721-3057

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0