## NSN 5305-00-721-4620

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-721-4620 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.281 inches **Fastener Length:** Between 0.797 inches and 0.828 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.110 inches and 0.122 inches **First Diameter From Head:** Between 0.115 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.547 inches and 0.578 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4140h **Material Specification:** Astm a304 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-721-4620

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0