NSN 5305-00-721-8346

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-721-8346

View Online at https://aerobasegroup.com/nsn/5305-00-721-8346
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.203 inches and 0.234 inches
Fastener Length:
Between 0.703 inches and 0.734 inches
Head Style:
Knurled no. 1
Head Diameter:
Between 0.734 inches and 0.766 inches
Head Height:
Between 0.234 inches and 0.266 inches
Shoulder Diameter:
0.375 inches first shoulder
Shoulder Length:
0.125 inches first shoulder
First Diameter From Head:
Between 0.182 inches and 0.187 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.484 inches and 0.516 inches
Point Style:
Flat
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Externally Relieved Body Diameter Quantity:
1
Shoulder Shape:
Round first shoulder
Material:
Steel comp 303
Material Specification:
Qq-s-764 cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
171, finish no. 5.4.1 military standard single treatment response
Thread Series Designator:
Unc

Unc

NSN 5305-00-721-8346

Thumbscrew - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0