

View Online at <https://aerobasegroup.com/nsn/5305-00-721-8461>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.295 inches

**Fastener Length:**

0.375 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.292 inches and 0.313 inches

**Head Height:**

Between 0.118 inches and 0.130 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

45.0 rockwell c primary washer and 53.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.283 inches and 0.297 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.040 inches

**Material:**

Steel comp 1010 bearing surface of head or steel comp 1011 bearing surface of head or steel comp 1013 bearing surface of head or steel comp 1015 bearing surface of head or steel comp 1016 bearing surface of head or steel comp 1017 bearing surface of head or steel comp 1018 bearing surface of head or steel comp 1019 bearing surface of head or steel comp 1020 bearing surface of head

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0