

NSN 5305-00-721-8461 Assembled Washer Screw - Page 1 of 2	AeroBase Group
View Online at https://aerobasegroup.com/nsn/5305-00-721-8461	
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.295 inches	
Fastener Length:	
0.375 inches	
Head Style:	
Fillister	
Head Diameter:	
Between 0.292 inches and 0.313 inches	
Head Height:	
Between 0.118 inches and 0.130 inches	
Washer Quantity:	
1	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.190 inches	
Thready Qty Per Inch (tpi):	
32	
Hardness Rating:	
45.0 rockwell c primary washer and 53.0 rockwell c primary washer	
Primary Washer Outside Diameter:	
Between 0.283 inches and 0.297 inches	
Primary Washer Style:	
Split helical ring	
Primary Washer Material Thickness:	
0.040 inches	
Material:	
Steel comp 1010 bearing surface of head or steel comp 1011 bearing surface of head or steel comp 1013 bearing	g surface of head or steel
comp 1015 bearing surface of head or steel comp 1016 bearing surface of head or steel comp 1017 bearing surface	ace of head or steel comp
1018 bearing surface of head or steel comp 1019 bearing surface of head or steel comp 1020 bearing surface of	head
Surface Treatment:	
Cadmium or zinc	
Surface Treatment Specification:	
Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification	1 2nd treatment response
Thread Series Designator:	
Unf	
Shelf Life:	

N/a

Unit Of Measure:

NSN 5305-00-721-8461

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

