NSN 5305-00-722-2413

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-722-2413 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.188 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 321.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5735 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Unit Of Measure:
-Demilitarization:
No

NSN 5305-00-722-2413

Machine Screw - Page 2 of 2



Fiig:

A500d0